











Zoom Lens

KEY FEATURES		GL-A80Z8C	GL-A60Z10C	GL-A80Z10C	GL-A100Z10C
<ul style="list-style-type: none"> • Auto Iris, Zoom • C / CS Mount • Excellent sharpness through variable contrast even at Wide Range 					
Model No.		GL-A80Z8C	GL-A60Z10C	GL-A80Z10C	GL-A100Z10C
Image Format		1/2"	1/3"	1/2"	1/2"
Focal Length		8~64 mm	6~60 mm	8~80 mm	10~100 mm
Maximum F value		1.6	1.4	1.6	1.6
Magnification		x8	x10	x10	x10
Angle of View	1/2"	Wide	33.2°x 44.0°	32.8°x 43.4°	26.5°x 35.1°
		Tele	4.4°x 5.8°	3.51°x 4.62°	2.84°x 3.74°
	1/3"	Wide	-	-	-
		Tele	-	-	-
Minimum Focal Distance		1 m	1 m	1 m	1 m
Back Focal Length		14.74 mm	12.98 mm	16.49 mm	15.80 mm
Mount		C	C	C	C
Iris Operation Method		Galvano	Galvano	Galvano	Galvano
Adjust Voltage		0.4~1.0Vp-p	0.4~1.0Vp-p	0.4~1.0Vp-p	0.4~1.0Vp-p
Operation Voltage		DC 6~12V	DC 6~12V	DC 6~12V	DC 6~12V
Operation Current		Max. 60mA	Max. 60mA	Max. 60mA	Max. 60mA
Dimensions		64 x 72 x 91.8 mm	65 x 68.5 x 103.5 mm	65 x 68.5 x 103.5 mm	65 x 66 x 121 mm
Weight		430g	430g	430g	515g
Preset Option		No	No	Yes	Yes
KEY FEATURES		GL-A110Z10(P)	GL-A100Z20(P)	GL-3M1021A(P)	
<ul style="list-style-type: none"> • Auto Iris, Zoom • C / CS Mount • Excellent sharpness through variable contrast even at Wide Range 					
Model No.		GL-A110Z10(P)	GL-A100Z20(P)	GL-3M1021A(P)	
Image Format		1/2"	1/2"	1/2"	
Focal Length		11~110 mm	10~200 mm	10~210 mm	
Maximum F value		1.8	1.8	1.5	
Magnification		x10	x20	x21	
Angle of View	1/2"	Wide	32.4°x 40.0°	35.7°x 44.4°	26.8°x 35.6°
		Tele	3.3°x 4.2°	1.9°x 2.3°	1.35°x 1.78°
	1/3"	Wide	24.2°x 30.0°	26.8°x 33.5°	20.2°x 26.8°
		Tele	2.6°x 3.2°	1.4°x 1.8°	1.02°x 1.35°
Minimum Focal Distance		1.3 m	1.5 m	2 m	
Back Focal Length		17.58 mm	14.39 mm	13.91 mm	
Mount		C	C	C	
Iris Operation Method		DC Motor	DC Motor	DC Motor	
Adjust Voltage		0.5~1.0Vp-p	0.5~1.0Vp-p	0.4~1.0Vp-p	
Operation Voltage		DC 8~18V	DC 8~18V	DC 6~12V	
Operation Current		Max. 50mA	Max. 50mA	Max. 60mA	
Dimensions		118 x 91.0 x 140.5 mm	78 x 93 x 159.5 mm	88 x 90.5 x 207.2 mm	
Weight		1,220g(1,260g)	880g(920g)	1,100g	
Preset Option		Yes	Yes	Yes	
KEY FEATURES		GL-3M1027A(P)	GL-3M1031AP	GL-A125Z60B/D/P	
<ul style="list-style-type: none"> • Auto Iris, Zoom • C / CS Mount • Excellent sharpness through variable contrast even at Wide Range 					
Model No.		GL-3M1027A(P)	GL-3M1031AP	GL-A125Z60B/D/P	
Image Format		1/2"	1/2"	1/2"	
Focal Length		10~270 mm	10~310 mm	12.5~750 mm	25~1500 mm
Maximum F value		3.5	1.5	3.8	7.6
Magnification		x27	x31	x60	
Angle of View	1/2"	Wide	28.0°x 37.0°	26.7°x 35.3°	21.44°x 28.43°
		Tele	0.80°x 1.4°	0.90°x 1.27°	0.22°x 0.29°
	1/3"	Wide	-	20.1°x 26.7°	16.23°x 21.44°
		Tele	-	0.68°x 0.90°	0.17°x 0.22°
Minimum Focal Distance		1.5 m	2.8 m	5 m	
Back Focal Length		24.58 mm	14.57 mm	53.23 mm	31.10 mm
Mount		C	C	C	
Iris Operation Method		DC Motor	DC Motor	DC Motor	
Adjust Voltage		0.4~1.0Vp-p	0.4~1.0Vp-p	0.4~1.0Vp-p	
Operation Voltage		DC 6~12V	DC 6~12V	DC 6V / DC12V	
Operation Current		Max. 60mA	Max. 60mA	Max. 450mA	
Dimensions		88 x 90.5 x 207.2 mm	97 x 109 x 238.5 mm	154 x 137 x 354 mm	
Weight		2,050g	2,100g	5,200g	
Preset Option		Yes	Default	Built-in Extender(x2) D: Day & Night, Preset P: Day & Night, PC Control, Preset	