

SPK-B30

Image



Key Features

- 1/3.6 Inch CMOS Sensor
- 656(H) x 492(V)
- f2.9mm Board Lens
- DC5V ~ DC24V Input
- Mirror Switch
- Flip Switch
- 7m Cable

Ordering Number

- SPK-B30NC : NTSC, f2.9mm, 7m Cable

Technical Specifications

	NTSC	PAL
VIDEO		
Imaging Device	1/3" CMOS Image Sensor	
Signal System	NTSC	PAL
Effective Pixels Number	656(H) x 492(V)	768(H) x 576(V)
Scanning System	2:1 Interlace	
Sync System	Internal	
Scanning Frequency	15.734KHz(H)/59.94Hz(V)	15.625KHz(H)/50Hz(V)
Horizontal Resolution	520TV Lines	600 TVLine
Min. Illumination	12V / Lux-sec	
S/N Ratio	More than 38dB (AGC OFF)	
Video output	CVBS : 1.0Vp-p / 75Ω Composite	
OPERATIONAL		
Electronic Shutter Speed	Rolling shutter	
Flickerless	Normal / Manual A / Manual B	
Brightness	Auto	
AGC	Support	
White Balance	AWC	
BLC	Support	
Day & Night	COLOR	
DNR	Auto	
MIRROR	OFF/ON	
FLIP	OFF/ON	
ENVIRONMENTAL		
Operating Temperature	-20℃ ~ +70℃	
Operating Humidity	Less than 80% RH	
ELECTRICAL		
Input Voltage	DC5V ~ DC24V	
Power Consumption	Max. 0.5W	
MECHANICAL		
Color	Black	
Material	PC+ABS	
Dimensions	φ30 x 52 mm	
Weight	T.B.D	

Dimensions

Unit : mm

