

## SPK-B33W

### Image



### Key Features

- 1/4 Inch CMOS Sensor
- WDR (Wide Dynamic Range)
- 640(H) x 480(V)
- f2.9mm Board Lens
- DC5V ~ DC24V Input
- Mirror Switch
- Flip Switch
- 7m Cable

### Ordering Number

- SPK-B33W : NTSC, f2.9mm, 7m Cable

### Technical Specifications

	NTSC	PAL
<b>VIDEO</b>		
Imaging Device	1/4 Inch CMOS Sensor	
Signal System	NTSC	PAL
Effective Pixels Number	640(H) x 480(V)	
Scanning System	2:1 Interlace	
Sync System	Internal	
Scanning Frequency	15.734KHz(H)/59.94Hz(V)	15.625KHz(H)/50Hz(V)
Horizontal Resolution	420TV Lines	
Min. Illumination	2.5 V / lux-sec	
S/N Ratio	More than 36dB (AGC OFF)	
Video output	CVBS : 1.0Vp-p / 75Ω Composite	
<b>OPERATIONAL</b>		
Shutter Type	Electronic Rolling Shutter	
Brightness	Auto	
AGC(Auto Gain Control)	Auto	
Backlight Compensation	WDR	
Wide Dynamic Range	120 [dB]	
White Balance	AWC	
D-Effect	Off / Mirror / Rotate / V-Flip (Option)	
<b>ENVIRONMENTAL</b>		
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F)	
Operating Humidity	Less than 80% RH	
<b>ELECTRICAL</b>		
Input Voltage	DC5V ~ DC24V	
Power Consumption	Max. 0.5W	
<b>MECHANICAL</b>		
Dimensions	35 x 52 mm	
Weight	T.B.D	

### Dimensions

Unit : mm

