

# SPQ-G134NN

## Image



## Key Features

- PIXELPLUS 1/3" CMOS Image Sensor
- 720 X 480 Pixel Array
- 2D DNR (Digital Noise Reduction)
- WDR (Wide dynamic range)
- AUDIO (Option)
- OSD (Option)
- 3.6mm Board lens
- 30x30 Square

## Technical Specifications

	SPQ-G134NN	SPQ-G134NP
<b>VIDEO</b>		
Imaging Device	1/3" WDR CMOS Image Sensor	
Signal System	NTSC	PAL
Total Pixels	756(H) x 504(V)	756(H) x 504(V)
Effective Pixels Number	756(H) x 504(V)	756(H) x 504(V)
Scanning System	2:1 Interlace	
Sync System	Internal	
Scanning Frequency	15.734KHz(H)/59.94Hz(V)	15.625KHz(H)/50Hz(V)
Horizontal Resolution	560TV Lines	
Sensitivity	11.1[v/lUX.sec]	
S/N Ratio	47.9[dB]	
Video output	CVBS : 1.0Vp-p / 75Ω Composite	
<b>BOARD LENS</b>		
Mount Type	Board (M12 X 0.5Pitch)	
Lens Type	Fixed	
Focal length	3.6mm	
Max. Aperture Ratio	F2.0	
<b>OPERATIONAL</b>		
Electronic Shutter Speed	Rolling shutter	
Flickerless	Normal / Manual A / Manual B	
Brightness	Auto	
AGC	Support	
White Balance	AWC	
AUDIO	Support	
BLC	OFF/ON	
Day & Night	COLOR	
DNR	Auto	
MIRROR	Support	
FLIP	Support	
<b>ENVIRONMENTAL</b>		
Operating Temperature	-20℃ ~ +70℃	
Operating Humidity	Less than 80% RH	
<b>ELECTRICAL</b>		
Input Voltage	DC12V	
Power Consumption	Max. 1W	

## Dimensions

Unit : mm

